

STRATHEARN

— STONE AND TIMBER.CO.UK —

**PREFINISHED
AND
UNFINISHED
PARQUET
AND
CASSETTE
PRODUCT
RANGE
SHEETS**

STRATHEARN

— STONE AND TIMBER.CO.UK —

STRATHEARN PRODUCT RANGE SHEET: PREFINISHED PARQUET & CASSETTES OAK FLOORING COLLECTION

Strathearn prefinished oak parquet and cassette collection is a new generation of classic flooring with all the finest qualities of the original, reflected in designs ranging from sleek and contemporary to absolute authenticity, in patterns like traditional Versailles. The entire range is complemented by our extensive parquet design and installation expertise.

Available in a range of options, sizes and thickness. Bespoke sizes and extra large available eg 900x260mm.



ENGINEERED PREFINISHED OAK - PRICE PER M²

Sizes mm	Alsace Block	Alsace Chevron	Beaulieu & Chambord Block	Beaulieu & Chambord Chevron	Dijon Block	Dijon Chevron
70x470, 100x500, 100x600 & 120x730x16mm	£69.00	-	£78.00	-	£64.00	-
70x390, 100x490 & 120x600x16mm	-	£84.00	-	£92.00	-	£78.00

All prices exclude VAT

Lead time 5-6 weeks, Block/Chevron 6-8 weeks

When ordering include 5-10% for wastage & cuts

16mm Cassettes available in Alsace, Beaulieu & Chambord ranges (£145.00 per m²+VAT), Dijon range (£130.00 per m²+VAT)
21mm Cassettes available in Alsace, Beaulieu & Chambord ranges (£150.00 per m²+VAT), Dijon range (£135.00 per m²+VAT)
20mm block/chevron £POA, please enquire.

STRATHEARN

— STONE AND TIMBER.CO.UK —

TECHNICAL INFORMATION	Engineered 16 mm	Engineered 20 mm
Suitable for use with underfloor heating	✓	✓
Kiln dried to a moisture content 8-12%	✓	✓
Solid oak top layer thickness	4 mm	6 mm
Tongue and groove on 4 sides (Block Only)	✓	✓
Installation by gluing directly onto structural grade subfloor	✓	✓
Sub-floor must be perfectly even level and smooth (screed, chipboard or ply)	✓	✓
Installed with border (skirtings can be on or off)	✓	✓
Installed without border (skirtings must be off)	✓	✓
Design and installation by professional floor installer only	✓	✓

Note

Prefinished blocks, chevron & cassettes require one coat of oil following installation.

STORAGE & ACCLIMATISATION

We recommend that our engineered oak flooring is delivered at least 48 hours before fitting to allow the timber to acclimatise. During the recommended acclimatisation period, all oak must be stored flat in the area where installation is planned, and room temperature and humidity levels should be as per normal living conditions - slit open packs however do not remove blocks/boards entirely from plastic pack.

CLEANING

- An oil finish on oak floors should be left after application to 'cure' for 10-14 days before using any cleaning or care products.
- Sweep, vacuum or dust oak floors regularly. Micro-fibre mops are ideal for wood floors however dampen mop slightly rather than saturating. We recommend using Osmo Wash and Care cleaner or Osmo Spray Mop.
- Always wipe accidental spills immediately using a soft, slightly damp cloth.

MAINTENANCE

For areas of high traffic and stubborn stains apply Osmo Liquid Wax. It is possible to apply further coats of oil to refresh your floor – contact us for more information.

PROTECTING

The key to a beautiful, long lasting and hardwearing oak floor is a stable environment. Extremes of temperature and humidity cause wood to shrink and leave unwanted spaces between boards, while excessive humidity warps wood creating a 'waved' appearance. To keep your oak floor in 'just laid' condition, follow these simple rules.

- Maintain consistent room humidity between 35% and 65%.
- Keep underfloor heating switched on all year round.
- Do not place heavy rugs on oak floors with underfloor heating.
- Place felt floor pads under furniture for damage-free moving.
- Avoid walking on oak floors with stiletto heels, golf spikes and cleats. Clip pets' claws to prevent scratches.
- Never place potted plants directly onto oak floors.

STRATHEARN

— STONE AND TIMBER.CO.UK —

STRATHEARN PRODUCT RANGE SHEET: UNFINISHED PARQUET OAK FLOORING COLLECTION

Strathearn's oak parquet collection is all the beauty and elegance of this classic flooring reinvented for the 21st Century, in a wide range of contemporary and traditional patterns. Hand finished by Strathearn in-situ with a choice of exclusive oils, parquet is a perfect fit for new homes and brings effortless authenticity to traditional properties.

Available in a range of options, sizes and thickness. Bespoke sizes and extra large available eg 900x260mm.



	ENGINEERED UNFINISHED BLOCK – PRICE PER M ²		SOLID UNFINISHED BLOCK – PRICE PER M ²	
Sizes mm	Natural Grade	Prime Grade	Natural Grade 22mm	Prime Grade 22mm
70x280x20mm	£62.00	£69.00	£61.00	£69.00
500x100x20mm	£68.00	£77.00	-	-

All prices exclude VAT | *Lead time variable please check for details* | *When ordering include 10-15% for wastage and cuts*

Please enquire for installation, finish service and costs.

For our prefinished parquet/chevron please see our Alsace, Beaulieu, Chambord and Dijon ranges.

STRATHEARN

— STONE AND TIMBER.CO.UK —

TECHNICAL INFORMATION	Solid 20mm	Engineered 20 mm
Suitable for use with underfloor heating	-	✓
Kiln dried to a moisture content 8-12%	✓	✓
Solid oak top layer thickness	20 mm	6 mm
Tongue and groove on 4 sides (Block Only)	✓	✓
Installation by gluing directly onto structural grade subfloor	✓	✓
Sub-floor must be perfectly even level and smooth (screed, chipboard or ply)	✓	✓
Installed with border (skirtings can be on or off)	✓	✓
Installed without border (skirtings must be off)	✓	✓
Design and installation by professional floor installer only	✓	✓

Note

Unfinished square edge blocks require to be filled, sanded and oiled (2 coats) following installation.

GRADES

Natural Grade: Healthy sound & black knots up to 50mm, open filled knots, end cracks filled, sapwood up to 1/3 of width.

Prime Grade: Healthy sound knots up to 10mm. Black pin knots to 5mm. Sapwood up to 5% of board

STORAGE & ACCLIMATISATION

We recommend that our solid oak flooring is delivered at least two weeks before fitting to allow the timber to acclimatise. For engineered oak allow a minimum period of 48 hours. During the recommended acclimatisation period, all oak must be stored flat in the area where installation is planned, and room temperature and humidity levels should be as per normal living conditions - slit open packs however do not remove blocks/boards entirely from plastic pack.

CLEANING

- An oil finish on oak floors should be left after application to 'cure' for 10-14 days before using any cleaning or care products.
- Sweep, vacuum or dust oak floors regularly. Micro-fibre mops are ideal for wood floors however dampen mop slightly rather than saturating. We recommend using Osmo Wash and Care cleaner or Osmo Spray Mop.
- Always wipe accidental spills immediately using a soft, slightly damp cloth.

REPAIRING & REFRESHING

Light scratches and marks on oiled floors can be easily removed with gentle sanding and careful re-application of our recommended oil finish.

PROTECTING

The key to a beautiful, long lasting and hardwearing oak floor is a stable environment. Extremes of temperature and humidity cause wood to shrink and leave unwanted spaces between boards, while excessive humidity warps wood creating a 'waved' appearance. To keep your oak floor in 'just laid' condition, follow these simple rules.

- Maintain consistent room humidity between 35% and 65%.
- Keep underfloor heating switched on all year round.
- Do not place heavy rugs on oak floors with underfloor heating.
- Place felt floor pads under furniture for damage-free moving.
- Avoid walking on oak floors with stiletto heels, golf spikes and cleats. Clip pets' claws to prevent scratches.
- Never place potted plants directly onto oak floors.