

STRATHEARN

— STONE AND TIMBER.CO.UK —

Express Oak Specification Sheet

| | |
|--------------------|----------------------------------|
| Product | Balmoral |
| Engineered/Solid | Engineered |
| Plank sizes | 190x14mm |
| Herringbone sizes | N/A |
| Chevron sizes | N/A |
| Other sizes | N/A |
| Pack Size | 190x14mm 2.888m ² |
| Grades available | Nature Grade Only |
| Finishes available | Brushed |
| Oil finish | Hardened Oil |
| Species | Sustainably Sourced European Oak |

| | Plank |
|---|--------------------|
| Suitable for use with UFH | ✓ |
| Kiln dried to a moisture content 8-12% | ✓ |
| Solid oak top layer thickness | 3-4mm |
| End-matched timber (tongue & groove on 4 sides) | ✓ |
| Lengths | Random up to 1.86m |
| Micro-bevelled board edges, as standard | ✓ |
| Hand-scraped surface and edges optional for aged finish | × |
| Structural grade – install directly onto joists ≤ 400mm centres | × |
| Installation by secret nail onto suitable timber subfloor | × |
| Installation by gluing directly onto subfloor | ✓ |
| Installation as a floating floor - room area ≤ 30m ² , room width ≤ 4.5m | ✓ |
| Construction | 3 Layer |

Bespoke materials available e.g. nosing, treads, edging pieces, radiator roses

We do not advise to mix different batches in one floor area

For further information on grades & finishes please see our website

Plank Product Page

[Click Here](#)

For care and maintenance information

[Click Here](#)