STRATHEARN

— STONE AND TIMBER.CO.UK —

Choice Oak Specification Sheet

Product	Beaulieu Cl	Beaulieu Chantilly		
Engineered/Solid	Engineered			
	220x16mm	.40x 16mm / 180x16mm / 220x16mm / 180x20mm / 220x20mm / 260x20mm		
Plank sizes				
Herringbone sizes		470x70x16mm / 500x100x16mm / 600x100x16mm / 730x120x16mm		
Chevron sizes	410x70x16r 640x120x16	0x16mm / 520x100x16mm / 20x16mm		
Other sizes	Cassette	ette		
Pack Size	Random, or	n, order to nearest m2		
Grades available	Natural / Pr	l / Prime		
Finishes available	Standard / I	ard / Brushed		
Oil finish	Hard Wax C	ard Wax Oil		
Species	Sustainably	Sourced Eur	opean Oak	
		16mm	20mm	
Suitable for use with UFH		✓	✓	
Kiln dried to a moisture content 8-12%		✓	✓	
Solid oak top layer thickness		4mm	6mm	
End-matched timber (tongue & groove on 4 sides)		\checkmark	\checkmark	
Lengths		Random up to 2.4m		
Micro-bevelled board edges, as standard		✓	\checkmark	
Hand-scraped surface and edges optional for aged finish		×	×	
Structural grade – install directly onto joists ≤ 400mm centres		×	✓	
Installation by secret nail onto suitable timber subfloor		×	\checkmark	

Bespoke materials available e.g. nosing, treads, edging pieces - please enquire

 \checkmark

 \checkmark

Multi Ply

~

~

Multi ply

Installation by gluing directly onto timber or concrete subfloor

Construction

Installation as a floating floor - room area $\leq 30m^2$, room width $\leq 4.5m$

We do not advise to mix different batches in one floor area

For further information on grades & finishes please see our website

Product Page	<u>Click Here</u>
For care and maintenance information	Click Here

Strathearn Stone Timber Ltd. The Workshop, Forteviot, Perthshire PH2 9BT 01764 684836 info@stoneandtimber.co.uk www.stoneandtimber.co.uk REV: 07/07/2023