

Choice Oak Specification Sheet

Product Beaulieu 0	ulieu Cognac	
Engineered/Solid Engineere	ngineered	
220x16mr	m / 180x16mm / m / 180x20mm / m / 260x20mm	
	16mm / 500x100x16mm / x16mm / 730x120x16mm	
410x70x16 Chevron sizes 640x120x2	6mm / 520x100x16mm / L6mm	
Other sizes Manoir* /	noir* / Cassette	
*ultra-wide mixed width, ultra-long and engineered with 3 layers		
Pack Size Random, o	order to nearest m2	
Grades available Natural / F	Prime	
Finishes available Standard ,	/ Brushed	
Oil finish Hard Wax	Vax Oil	
Species Sustainable	Sustainably Sourced European Oak	
	16mm	20mm
Suitable for use with UFH	✓	✓
Kiln dried to a moisture content 8-12%	✓	✓
Solid oak top layer thickness	4mm	6mm
End-matched timber (tongue & groove on 4 sides)	✓	✓
Lengths	Random ι	ıp to 2.4m
Micro-bevelled board edges, as standard	✓	✓
Hand-scraped surface and edges optional for aged finish	×	×
Structural grade – install directly onto joists ≤ 400mm centres	×	✓
Installation by secret nail onto suitable timber subfloor	×	✓
Installation by gluing directly onto timber or concrete subfloor	✓	✓
Installation as a floating floor - room area ≤ 30m², room width ≤ 4.5m	✓	✓
Construction	Multi Ply	Multi ply

Bespoke materials available e.g. nosing, treads, edging pieces - please enquire

We do not advise to mix different batches in one floor area

For further information on grades & finishes please see our website

Product Page

Click Here

For care and maintenance information

Click Here

Strathearn Stone Timber Ltd. The Workshop, Forteviot, Perthshire PH2 9BT 01764 684836 info@stoneandtimber.co.uk www.stoneandtimber.co.uk REV: 07/07/2023