STRATHEARN

— STONE AND TIMBER.CO.UK —

Choice Oak Specification Sheet

Product	Chambord Armagnac		
Engineered/Solid	Engineered		
Plank sizes		x 16mm / 180x16mm / x16mm / 180x20mm / x20mm	
Herringbone sizes		470x70x16mm / 500x100x16mm / 600x100x16mm / 730x120x16mm	
Chevron sizes		0x70x16mm / 520x100x16mm / 0x120x16mm	
Other sizes	Manoir* / (Manoir* / Cassette	
*ultra-wide mixed width, ultra-long and engineered with 3 layers			
Pack Size	Random, or	Random, order to nearest m2	
Grades available	Natural		
Finishes available	Standard		
Oil finish	Hard Wax Oil		
Species	Sustainably Sourced European Oak		
		16mm	20mm
Suitable for use with UFH		√	\checkmark
Kiln dried to a moisture content 8-12%		✓	✓
Solid oak top layer thickness		4mm	6mm
End-matched timber (tongue & groove on 4 sides)		✓	✓
Lengths		Random up to 2.4m	
Micro-bevelled board edges, as standard		✓	✓
Hand-scraped surface and edges optional for aged finish		×	×
Structural grade – install directly onto joists ≤ 400mm centres		×	\checkmark
Installation by secret nail onto suitable timber subfloor		×	✓
Installation by gluing directly onto timber or concrete subfloor		\checkmark	\checkmark
Installation as a floating floor - room area $\leq 30m^2$, room width $\leq 4.5m$		\checkmark	\checkmark
Construction		Multi Ply	Multi ply

Bespoke materials available e.g. nosing, treads, edging pieces - please enquire

We do not advise to mix different batches in one floor area

For further information on grades & finishes please see our website

Product Page	<u>Click Here</u>
For care and maintenance information	Click Here

Strathearn Stone Timber Ltd. The Workshop, Forteviot, Perthshire PH2 9BT 01764 684836 info@stoneandtimber.co.uk www.stoneandtimber.co.uk REV: 07/07/2023