STRATHEARN

STONE AND TIMBER.CO.UK

Choice Oak Specification Sheet

Product	Chambord Bourgogne		
Engineered/Solid	Engineered		
	140x 16mm	0x 16mm / 180x16mm /	
	220x16mm / 180x20mm /		
Plank sizes	220x20mm / 260x20mm		
	470x70x16mm / 500x100x16mm /		
Herringbone sizes	600x100x16mm / 730x120x16mm		
	410x70x16mm / 520x100x16mm /		
Chevron sizes	640x120x16mm		
	Manoir* / Cassette		
*ultra-wide mixed width, ultra-long and engineered with 3 layers	-		
Pack Size	Random, order to nearest m2		
	Natural		
	Standard /Chateux**		
	Hard Wax Oil		
**same specification as Manoir but with a traditional mill surface, three-dimensional finish and variable thickness between 19 and 23mm			
Species Sustainably Sourced European Oak			
		1 (100 100	20 ma ma
Suitable for use with UFH		16mm ✓	20mm ✓
Kiln dried to a moisture content 8-12%		▼ ✓	▼ ✓
Solid oak top layer thickness		4mm	6mm
End-matched timber (tongue & groove on 4 sides)		411111	
Lengths		Random u	n to 2 /m
Micro-bevelled board edges, as standard			ip to 2.4m
Hand-scraped surface and edges optional for aged finish		×	×
Structural grade – install directly onto joists \leq 400mm centres		×	^ ✓
Installation by secret nail onto suitable timber subfloor		×	· ✓
Installation by gluing directly onto timber or concrete subfloor		~ ✓	· ✓
Installation as a floating floor - room area $\leq 30m^2$, room width $\leq 4.5m$		✓	✓ ✓
Construction		Multi Ply	Multi ply

Bespoke materials available e.g. nosing, treads, edging pieces - please enquire

We do not advise to mix different batches in one floor area

For further information on grades & finishes please see our website

Product Page For care and maintenance information

Click Here Click Here

Strathearn Stone Timber Ltd. The Workshop, Forteviot, Perthshire PH2 9BT 01764 684836 info@stoneandtimber.co.uk www.stoneandtimber.co.uk REV: 07/07/2023