

STRATHEARN

— STONE AND TIMBER.CO.UK —

Choice Oak Specification Sheet

Product	Chambord Calvados
Engineered/Solid	Engineered
Plank sizes	140x 16mm / 180x16mm / 220x16mm / 180x20mm / 220x20mm
Herringbone sizes	470x70x16mm / 500x100x16mm / 600x100x16mm / 730x120x16mm
Chevron sizes	410x70x16mm / 520x100x16mm / 640x120x16mm
Other sizes	Cassette
*ultra-wide mixed width, ultra-long and engineered with 3 layers	
Pack Size	Random, order to nearest m2
Grades available	Natural
Finishes available	Standard
Oil finish	Hard Wax Oil
Species	Sustainably Sourced European Oak

	16mm	20mm
Suitable for use with UFH	✓	✓
Kiln dried to a moisture content 8-12%	✓	✓
Solid oak top layer thickness	4mm	6mm
End-matched timber (tongue & groove on 4 sides)	✓	✓
Lengths	Random up to 2.4m	
Micro-bevelled board edges, as standard	✓	✓
Hand-scraped surface and edges optional for aged finish	x	x
Structural grade – install directly onto joists ≤ 400mm centres	x	✓
Installation by secret nail onto suitable timber subfloor	x	✓
Installation by gluing directly onto timber or concrete subfloor	✓	✓
Installation as a floating floor - room area ≤ 30m ² , room width ≤ 4.5m	✓	✓
Construction	Multi Ply	Multi ply

Bespoke materials available e.g. nosing, treads, edging pieces - please enquire

We do not advise to mix different batches in one floor area

For further information on grades & finishes please see our website

Product Page

[Click Here](#)

For care and maintenance information

[Click Here](#)

Strathearn Stone Timber Ltd. The Workshop, Forteviot, Perthshire PH2 9BT

01764 684836 info@stoneandtimber.co.uk www.stoneandtimber.co.uk

REV: 07/07/2023