

STRATHEARN

STONE AND TIMBER.CO.UK

Choice Oak Specification Sheet

Product	Chambord Limousin
Engineered/Solid	Engineered
Plank sizes	140x 16mm / 180x16mm / 220x16mm / 180x20mm / 220x20mm / 260x20mm
Herringbone sizes	470x70x16mm / 500x100x16mm / 600x100x16mm / 730x120x16mm
Chevron sizes	410x70x16mm / 520x100x16mm / 640x120x16mm
Other sizes	Manoir* / Cassette
*ultra-wide mixed width, ultra-long and engineered with 3 layers	
Pack Size	Random, order to nearest m2
Grades available	Natural
Finishes available	Standard /Chateux**
Oil finish	Hard Wax Oil
**same specification as Manoir but with a traditional mill surface, three-dimensional finish and variable thickness between 19 and 23mm	
Species	Sustainably Sourced European Oak

	16mm	20mm
Suitable for use with UFH	✓	✓
Kiln dried to a moisture content 8-12%	✓	✓
Solid oak top layer thickness	4mm	6mm
End-matched timber (tongue & groove on 4 sides)	✓	✓
Lengths	Random up to 2.4m	
Micro-bevelled board edges, as standard	✓	✓
Hand-scraped surface and edges optional for aged finish	×	×
Structural grade – install directly onto joists ≤ 400mm centres	×	✓
Installation by secret nail onto suitable timber subfloor	×	✓
Installation by gluing directly onto timber or concrete subfloor	✓	✓
Installation as a floating floor - room area ≤ 30m ² , room width ≤ 4.5m	✓	✓
Construction	Multi Ply	Multi ply

Bespoke materials available e.g. nosing, treads, edging pieces - please enquire

We do not advise to mix different batches in one floor area

For further information on grades & finishes please see our website

Product Page

[Click Here](#)

For care and maintenance information

[Click Here](#)

Strathearn Stone Timber Ltd. The Workshop, Forteviot, Perthshire PH2 9BT

01764 684836 info@stoneandtimber.co.uk www.stoneandtimber.co.uk

REV: 07/07/2023