

STRATHEARN

— STONE AND TIMBER.CO.UK —

Choice Oak Specification Sheet

Product	Dijon Ancien
Engineered/Solid	Engineered
Plank sizes	140x 16mm / 180x16mm / 220x16mm / 180x20mm / 220x20mm
Herringbone sizes	470x70x16mm / 500x100x16mm / 600x100x16mm 730x120x16mm
Chevron sizes	410x70x16mm / 520x100x16mm / 640x120x16mm
Other sizes	Cassette
Pack Size	Random, order to whole m2
Grades available	Natural / Prime
Finishes available	Hand Scraped
Oil finish	Hard Wax Oil
Species	Sustainably Sourced European Oak

	16mm	20mm
Suitable for use with UFH	✓	✓
Kiln dried to a moisture content 8-12%	✓	✓
Solid oak top layer thickness	4mm	6mm
End-matched timber (tongue & groove on 4 sides)	✓	✓
Lengths	Random up to 2.4m	
Micro-bevelled board edges, as standard	x	x
Hand-scraped surface and edges for aged finish	✓	✓
Structural grade – install directly onto joists ≤ 400mm centres	x	✓
Installation by secret nail onto suitable timber subfloor	x	✓
Installation by gluing directly onto timber or concrete subfloor	✓	✓
Installation as a floating floor - room area ≤ 30m ² , room width ≤ 4.5m	✓	✓
Construction	Multi Ply	Multi ply

Bespoke materials available e.g. nosing, treads, edging pieces - please enquire

We do not advise to mix different batches in one floor area

For further information on grades & finishes please see our website

Product Page

[Click Here](#)

For care and maintenance information

[Click Here](#)