

Choice Oak Specification Sheet

Product Dijon Gris	Dijon Gris		
Engineered/Solid Engineered	Engineered		
220x16mm	5mm / 180x16mm / mm / 180x20mm / mm / 260x20mm		
	16mm / 500x100x16mm / x16mm / 730x120x16mm		
410x70x16 Chevron sizes 640x120x1	6mm / 520x100x16mm / L6mm		
Other sizes Manoir* / 0	Manoir* / Cassette		
*ultra-wide mixed width, ultra-long and engineered with 3 layers			
Pack Size Random, o	m, order to nearest m2		
Grades available Natural / P	/ Prime		
Finishes available Standard /	dard / Brushed		
Oil finish Hard Wax (Hard Wax Oil		
Species Sustainably		Sourced European Oak	
	16mm	20mm	
Suitable for use with UFH	✓	✓	
Kiln dried to a moisture content 8-12%	✓	✓	
Solid oak top layer thickness	4mm	6mm	
End-matched timber (tongue & groove on 4 sides)	✓	✓	
Lengths	Random u	ıp to 2.4m	
Micro-bevelled board edges, as standard	✓	✓	
Hand-scraped surface and edges optional for aged finish	×	×	
Structural grade – install directly onto joists ≤ 400mm centres	×	✓	
Installation by secret nail onto suitable timber subfloor	×	✓	
Installation by gluing directly onto timber or concrete subfloor	✓	✓	
Installation as a floating floor - room area ≤ 30m², room width ≤ 4.5m	✓	✓	
Construction	Multi Ply	Multi ply	

Bespoke materials available e.g. nosing, treads, edging pieces - please enquire

We do not advise to mix different batches in one floor area

For further information on grades & finishes please see our website

Product Page <u>Click Here</u>