

STRATHEARN

— STONE AND TIMBER.CO.UK —

Express Oak Specification Sheet

Product	Scone
Engineered/Solid	Engineered
Plank sizes	190x14mm
Herringbone sizes	N/A
Chevron sizes	N/A
Other sizes	N/A
Pack Size	190x14mm 2.888m ²
Grades available	Nature Grade Only
Finishes available	Brushed
Oil finish	Hardened Oil
Species	Sustainably Sourced European Oak

	Plank
Suitable for use with UFH	✓
Kiln dried to a moisture content 8-12%	✓
Solid oak top layer thickness	3-4mm
End-matched timber (tongue & groove on 4 sides)	✓
Lengths	Random up to 1.86m
Micro-bevelled board edges, as standard	✓
Hand-scraped surface and edges optional for aged finish	×
Structural grade – install directly onto joists ≤ 400mm centres	×
Installation by secret nail onto suitable timber subfloor	×
Installation by gluing directly onto subfloor	✓
Installation as a floating floor - room area ≤ 30m ² , room width ≤ 4.5m	✓
Construction	3 Layer

Bespoke materials available e.g. nosing, treads, edging pieces, radiator roses

We do not advise to mix different batches in one floor area

For further information on grades & finishes please see our website

Plank Product Page

[Click Here](#)

For care and maintenance information

[Click Here](#)